





ISOMETRIC VIEW

Description

ACO Cablemate® Lid Cement Concrete Communications 13

ACO Cablemate[®] Lid Cement Concrete Blank ¹³

ACO Cablemate® Lid Cement Concrete Eletricity 13

Load Class	Туре	Description	Overall Length (mm)	Overall Width (mm)	Overall Depth (mm)	Clear Length (mm)	Clear Width (mm)	Clear Depth (mm)	Weight (kg)	Pallet (Units)	Part Number
A to B*	Type 43	ACO Cablemate® Pit Type 43	430	430	606	343	343	544	4.00	-	74308

Load Class	Туре	Description	Overall Length (mm)	Overall Width (mm)	Overall Depth (mm)	Clear Length (mm)	Clear Width (mm)	Clear Depth (mm)	Weight (kg)	Pallet (Units)	Part Number
A to B*	Type 43	ACO Cablemate® Pit Type 43	430	430	606	343	343	544	4.00	-	74308
* Check the Lide lead elected											

1. Refer to ACO Cablemate® literature for details

ACO Cablemate[®] Lid Steel ¹⁴

4. Lia dimension:	389 dia x 54 (mm)	
	Drawn: Danilo V.	Revision: 00
	Verified:	Date:

18

18

3. Lid dimension: 389 dia x 61 (mm)

SPECIFICATION SHEET

2. Lifting weight - kg

George S. April/21

18

18

Weight Cover ² | Weight Total

Part

Number

76221

74592

74312

74320

Brand:

ACO CABLEMATE®

B80

Product:

ACO CABLEMATE®

Polyethylene Pit Type 43

Materials/Properties

The pit body shall be manufactured from polyethylene with:

Flexural strength: 15MPa Electrical resistivity = $1 \times 10^{16} \Omega / \text{sq}$

Polyethylene moulded pits feature a ribbed construction for strength and durability.

Frost proof

Salt proof Surface burn characteristics of the material shall comply with UL 723

The cable pit shall be installed in accordance with the manufacturer's installation instructions and recommendations.

The cable pit shall be ACO Cablemate® Type 43 with lid/access cover* (see below) as manufactured by ACO Pty Ltd. or equal approved.

Water absorption 0.31% Dilute acid and alkali resistant

IP ratings up to IP4X (AS 60529) - enclosure protection against ingress

The nominal clear opening shall be 343mm dia. Units shall be manufactured with a clear depth of 544mm.

The pit shall be covered with a CableMate® cement concrete/steel lid - see table for compatible options.

Compatible Lids and Access Covers

ACO Limited Unit F/6 Percival Gull Place Mangere Auckland 2022 Tel: 0800 448 080

Fax: +64 9255 5114 Email: info@aconz.co.nz