


# Type 6 polyethylene cable pit

## Cable pit



**Key**

- ① Clear working dimension at pit base
- ② Clear working dimension at pit opening
- ③ Clear working dimension beneath rebate
- ④ Clear working dimension beneath riser cut off point
- ⑤ Height above retrorib

ACO Specification Information

**Type 6 polyethylene cable pit**

ACO Specification Information

**Cable pit and riser**

Description	Part No	Depth mm	Weight kg
Type 6 polyethylene pit	<b>75475</b>	670	33.0

**Compatible lids and access covers**

Description	Part No	Weight kg	
		cover <sup>2</sup>	total
Cement concrete 2-part lid (AS 3996 Cl A) - Blank <sup>1 3</sup>	<b>75010</b>	33	69
Cement concrete 2-part lid (AS 3996 Cl A) - Communications <sup>1 3</sup>	<b>75011</b>	33	69
Cement concrete 2-part lid (AS 3996 Cl A) - Electricity <sup>1 3</sup>	<b>75012</b>	33	69
Steel 2-part lid (AS 3996 Cl B) <sup>1 4</sup>	<b>76820</b>	15	31
Steel 2-part lid (AS 3996 Cl C) <sup>1 4</sup>	<b>custom</b>	-	-
Steel PowerLok 2-part lid (AS 3996 Cl B) <sup>1 4</sup>	<b>76830</b>	20	40
Steel PowerLok 2-part lid (AS 3996 Cl C) <sup>1 4</sup>	<b>custom</b>	-	-
Steel Urbanfil 2-part recessed cover (AS 3996 Cl B) <sup>1</sup>	<b>82567</b>	13	39
Steel Pavermate 2-part recessed cover (AS 3996 Cl B) <sup>1</sup>	<b>82373</b>	15	41
Ductile iron Rhinocast 2-part recessed cover (AS 3996 Cl B) <sup>1</sup>	<b>85433</b>	30	91
Ductile iron Rhinocast 2-part solid top cover (AS 3996 Cl B) <sup>1</sup>	<b>86853</b>	28	89

1. Refer to ACO Cablemate literature for details
2. Lifting weight - kg
3. Lid dimension: 651 x 499 x 50 (mm)
4. Lid dimension: 655 x 500 x 48 (mm)

**Specifications**

*General*  
The cable pit shall be ACO Cablemate Type 6 with lid/access cover\* (see below) as manufactured by ACO Pty Ltd. or equal approved.

*Materials*  
The pit body shall be manufactured from polyethylene with:

Electrical resistivity 1 x 10<sup>16</sup> Ω/sq  
 Flexural strength: 15MPa  
 Water absorption 0.31%  
 Frost proof  
 Salt proof  
 Dilute acid and alkali resistant  
 Surface burn characteristics of the material shall comply with UL 723  
 IP ratings up to IP4X (AS 60529) - enclosure protection against ingress

Polyethylene moulded pits feature a ribbed construction for strength and durability. The nominal clear opening shall be 1268mm x 455mm. Units shall be manufactured with a clear depth of 616mm.

*Lid/Access cover*  
The pit shall be covered with a cement concrete lid\*, steel lid\*, Urbanfil/Pavermate access cover\*, Rhinocast access cover\* - see table for compatible options.

*Installation*  
The cable pit shall be installed in accordance with the manufacturer's installation instructions and recommendations.

\* delete as applicable

**ACO Limited**  
**New Zealand**  
 Ph: 0800 448 080  
 www.aconz.co.nz  
 sales@aconz.co.nz

© October 2020 ACO Limited. All reasonable care has been taken in compiling the information in this document. All recommendations and suggestions on the use of ACO products are made without guarantee since the conditions of use are beyond the control of the company. It is the customer's responsibility to ensure that each product is fit for its intended purpose and that the actual conditions are suitable. ACO Limited. pursues a policy of continuous product development and reserves the right to amend specifications without notice.

